

FreshIQ[®]

2300 Series

Automated Protection for Refrigeration

NAMA
LISTED



Normally Unlocked
Lock Upon Fault



Normally Locked
With Select Access

Highlights:

- Retrofits to existing walk-in, reach-in, and integrated retail refrigerators
- Automated food safety compliance (NSF, NAMA, FDA compliant)
- 24/7 refrigeration monitoring - real time alerts for power loss, temperature, failures
- Remote visibility from any phone or PC to act before loss occurs
- Flexible security with both normally unlocked and normally locked products

At a Glance:

- Slim form factor – fits most coolers/freezers
- Remote monitoring & unlocking
- Event logging & activity alerts
- Easy Install by OEM or retrofit

FreshTraq[™] Portal



Designed and manufactured in USA by:



701 Gullo Ave.
Elk Grove Village, IL 60007

(847) 640-7002
sales@triteglock.com

www.freshiqlock.com

Applications:	Walk-in, reach-in, and integrated refrigerators
Temperature Sensor:	6 millimeter diameter stainless steel enclosure w/13' cable.
Primary Power:	120 VAC – 12V DC 500 mA wall-mount converter (supplied)
Back-up Power:	9 volt NiCad rechargeable (supplied)
Indicators:	Red LED flashing – Locked: Fault protection event Red LED On – Locked: Intentionally by key fob, no faults Green LED On – Unlocked: Monitoring for faults Red Green flashing – Unlocked: waiting for unit to reach temperature to begin monitoring
Cooler Protection Temperature:	41° F or greater for over 30 minutes
Restock Timer Extension:	30 minutes, programmed with intelligent logic to avoid non-fault lock events during defrost and high usage periods
Freezer Protection Temperature:	0° F or greater for over 30 minutes
Restock Timer Extension:	75 minutes, programmed with intelligent logic to avoid non-fault lock events during defrost and high usage periods
Primary Power Loss:	Automatically locks in 2 minutes, continues monitoring & automatically unlocks if power is restored before a protection locking event occurs
Data Logger:	Available with FreshTraq™
Remote Unlocking:	Available with FreshTraq™
Key:	Enabled TriTaq P1, Standard, Economy or AutoTraq key fobs for unlocking and independently/intentional locking
Test Switch:	For Health Department inspections – will trigger a lock event when pressed for 10 seconds
Mounting Hardware:	Miscellaneous fasteners provided
Approx. Time to Install & Test:	20 minutes
Certifications:	NAMA 2013 “Standard for Sanitary Design and Construction of Food and Beverage Vending Machines” and US Public Health Service “Food Code 2009”
Compliance:	UL Compliant with manual unlock button